

	<u>ENGLISH</u>	<u>SI</u>	
<b>Performance</b>			
Sensitivity(± 20 %)	10 mV/με	10 mV/με	
Measurement Range	300 pk με	300 pk με	[2]
Frequency Range(-5 %)	.004 Hz	.004 Hz	[3]
Broadband Resolution(1 to 10,000 Hz)	.001 nε	.001 nε	[1]
Non-Linearity	≤ 2 %	≤ 2 %	[4]
<b>Environmental</b>			
Temperature Range(Operating)	-65 to +250 °F	-54 to +121 °C	[1]
<b>Electrical</b>			
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Discharge Time Constant	≥ 150 sec	≥ 150 sec	
Electrical Isolation	≥ 10 <sup>8</sup> Ohm	≥ 10 <sup>8</sup> Ohm	
<b>Physical</b>			
Sensing Element	Quartz	Quartz	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Epoxy	Epoxy	
Size (Width x Length x Height)	.67 in x 1.725 in x .60 in	17 mm x 43.8 mm x 15 mm	
Weight(without cable)	2.0 oz	58 gm	[1]
Electrical Connector	Integral Cable	Integral Cable	
Electrical Connection Position	Side	Side	
Mounting	Through Hole	Through Hole	
Mounting Torque	7.38 ft-lb	10 Nm	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

[1] Typical.  
 [2] Based on 10 mV/με sensitivity.  
 [3] Calculated from discharge time constant.  
 [4] Zero-based, least-squares, straight line method.  
 [5] See PCB Declaration of Conformance PS023 for details.

**SUPPLIED ACCESSORIES:**  
 Model M081A100 M6 x 1.00 flathead screw (1)



*All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.  
 This model, designated with an RH prefix, is RoHS compliant. For further details, and to obtain PCB's RoHS Statement of Conformance, please visit <http://www.pcb.com>

Entered: AP	Engineer: GD	Sales: KWW	Approved: BAM	Spec Number:
Date: 7/22/2014	Date: 7/22/2014	Date: 7/22/2014	Date: 7/22/2014	<b>58626</b>

<p>3425 Walden Avenue, Depew, NY 14043</p>	<p><b>Phone: 716-684-0001</b>  <b>Fax: 716-684-0987</b>  <b>E-Mail: <a href="mailto:info@pcb.com">info@pcb.com</a></b></p>
--	--